COMPANICS
Communication & Electronics LTD

כומפניקס תקשורת ואלקטרוניקה בע"מ
הבורסקאי 1 א.ת. סגולה, פ"ת | ספק מ. הביטחון: 83524121 | ח.פ: 512109968
טל' / 03-9049004 | www.companics.co.il | sales@companics.co.il

Model Number: 06033
Multi-functions CCTV tester Wire Tracker

Feature:



לצפייה באתר לחץ כאן

- Secondary code digital mode, decisively rejects noise and false signals, locate cables quickly and easily
- Cable tracer and UTP cable test at the same time.
- Identify cable type:100M/1000M, straight/cross/other
- UTP/STP/RJ45/RJ11 cable scan and continuity testing
- Identify the status in the working telephone line: standby, ringing and off-hook
- Quickly detect the near-end, mid-end and far-end fault point of RJ45 cable connector
- UTP port support max 60V withstand voltage, the wire can be traced directly in connection with PoE switch
- Shielded cable and shielding layer continuity test
- Detect the short circuit of cable NEW
- Detect the link continuity of the switch port NEW
- PD powered detection: detect whether the power output of the POE switch is normal, and detect the pins used for power supply.
- Support silent mode
- Two bright LED lights for working in the dark

Specifications:

Item	Multi-functions CCTV tester Wire Tracker
Model	**06033**
Emit signal	Digital signal(rejects noise and false signals)
Cable type	RJ45 Twisted pair, RJ11 telephone line, BNC cable etc.
UTP cable test	The digital “1-8” for cable sequence shielded cable and shielding layer continuity indicator, check cable type indicator: straight/cross/other, 100M/1000M network cable test, and near-end, mid-end, far-end continuity testing, UTP cable short circuit test
Continuity test of RJ45 cable connectors	Detect the continuity of the pins on both sides of network cable and short circuits
PD (powered) test	PoE switch power supplying status test and check the pins used for power supply

Item	Multi-functions CCTV tester Wire Tracker
Model	**06033**
LED lamp	Short press On /Off LED light
Silent mode	Long press key "Mute" to switch silent mode, find cable through indicator
Audio output	Support external audio output
Power supply	
External power supply	Two AA batteries
General	
Working Temperature	-10℃---+50℃
Working Humidity	30%-90%
General	
Dimension	152mm x 62mm x 27mm /0.12KG
Receiver Dimension	218mm x 48mm x 32mm /0.1KG

Connection:


כניסת BNC
כניסת רשת RJ45
נוריות חיווי LOCAL/Remote
נורת חיווי, מצב טלפון RJ11
כניסת RJ11 Port
מתג פונקציות
נורת חיווי SWITCH
מד סוללה
נוריות חיווי לרציפות הכבל
כפתור SET
נוריות חיווי סוג חיבור
נורת חיווי סוג / מצב כבל
נוריות חיווי 100M/1000M
BNC
RJ45
LOCAL
REMOTE
SWITCH
STATUS
RJ11
SCAN/UTP
OFF
UTP
SET
DIRECT
CROSS
OTHER
100M
1000M
UTP/STP
Wire Tracker
EMITTER
נורת LED
נורת חיווי Power
נוריות חיווי לרציפות הכבל / מחוון עוצמת האות
נורת חיווי רציפות הסיכוך
יציאת אוזניות 3.5 מ"מ
כפתור הפעלה / רגישות
כניסת RJ11
כפתור השתק
כפתור הדלקה / כיבוי הפנס
נורות חיווי סוג החיבור
נורת חיווי הכבל
נוריות חיווי 100M/1000M
יציאת בדיקה מופעלת על ידי PD