










Material:

- 1.RJ45 Housing:PC
- 2.Phosphor Bronze with 50-60 micro-inch Nickel plated.
- 3.Contact area: 3-50 micro-inch Gold plated
- 4.IDC Housing: PC
- 5.IDC Terminal material & finished:
 - 5-1.Phosphor Bronze with 50 micro-inch Tin-Lead plated. Over 50-60 micro-inch Nickel plated.
 - 5-2.Use for 22-26 AWG stranded and solid wire
- 6.Jack Bracket Set:ABS
- 7.PCB: FR4 UL 94V0

Performance:

- a.The IDC color combine two wirings of T568A & T568B.
- b.Insertion Force: 900 grms for 8 contacts
- c.Retention Strength: 7.7kgs between Jack and Plug
- d. Operation Temperature: -40°C to 70°C.
- e.Durability:
 - e-1.Jack:750 cycles Plug-Jack mating and unmating test.
 - e-2. IDC: Max 200 punching times.



TITLE:			 Modle: 17393			
	INCH	MM				
.X	.015	.30				
.XX	.010	.10				
.XXX	.005	.05				
DRAWN BY	SHEN		P/N:			
CHECK BY			SCALE	1:1		REV
			UNIT	MM		
APPD BY			SHEET	1/1	DWG NO:	
			DATE	2020/05/05		