COMPANICS
Communication & Electronics LTD

כומפניקס תקשורת ואלקטרוניקה בע"מ
הבורסקאי 1 א.ת. סגולה, פ"ת | ספק מ. הביטחון: 83524121 | ח.פ: 512109968
03-9049004 / טל' | www.companics.co.il | sales@companics.co.il

Model Number 18116
4Kx2K 1x4 HDMI Splitter

Description:

This product distributes 1 way HDMI signal from STB, DVD, Blu Ray players or PS3 etc. to 4 way HDMI signal to connect to projector, DLP, LCD or other HD displays simultaneously.



Features:

- HDMI splitter & extender function
- HDMI splitter function
- 3D support
- CEC support
- 4K*2K support

לצפייה באתר לחץ כאן

Specifications:

Item		4Kx2K 1x4 HDMI Splitter
	Model	18116
Features	HDMI Splitter	Distribute 1 HDMI source to 4 HDMI displays simultaneously
	HDMI Extender	Extend HDMI signal up to 30 meters for input and 25 meters for output
	HDMI Resolution	Up to 4K X 2K and support full 3D fomat
	Energy-Saving	With energy-saving technology, power consumption is as low as 1W
Power	Power supply mode	Power adaptor 5V/1A
	Voltage	DC 5V
	Consumption	<5W
HDMI Input	HDCP Compliance	Yes
	HDMI Resolution support	480i@60Hz,480p@60Hz, 576i@50Hz,576p@50Hz, 720p@50/60Hz,1080i@50/60Hz, 1080p@50/60Hz,1080p@24Hz 3D, 720p@50/60Hz 3D, 4K X 2K
	HDMI graphic resolution support	640x480@60Hz,800x600@60Hz, 1024x768@60Hz, 1280x720@60Hz, 1280x768@60Hz,1280x960@60Hz, 1280x1024@60Hz,1360x768@60Hz, 1366x768@60Hz,1400x1050@60Hz, 1440x900@60Hz,1600x900@60Hz, 1680x1050@60Hz, 1920x1080@60Hz
	Color format support	24-bits /Deep color 30 bits/ Deep color 36-bits
	Max. Data rate	10.2Gbps
	TMDS signal	0.5~1.5Vp-p(TMDS)
	DDC signal	5Vp-p(TTL)
	The length for HDMI cable	<=30m(AWG26 standard HDMI cable)

HDMI Output	HDCP Compliance	Yes
	HDMI Resolution support	480i@60Hz,480p@60Hz, 576i@50Hz,576p@50Hz, 720p@50/60Hz,1080i@50/60Hz, 1080p@50/60Hz,1080p@24Hz 3D, 720p@50/60Hz 3D, 4K X 2K
	HDMI graphic resolution support	640x480@60Hz,800x600@60Hz, 1024x768@60Hz, 1280x720@60Hz, 1280x768@60Hz,1280x960@60Hz, 1280x1024@60Hz,1360x768@60Hz, 1366x768@60Hz,1400x1050@60Hz, 1440x900@60Hz,1600x900@60Hz, 1680x1050@60Hz, 1920x1080@60Hz
	Color format support	24-bits /Deep color 30 bits/ Deep color 36-bits
	Max. Data rate	10.2Gbps
	TMDS signal	0.5~1.5Vp-p(TMDS)
	DDC signal	5Vp-p(TTL)
	The length for HDMI cable	<=25m(AWG26 standard HDMI cable)
Protection Prot	ESD protection	1a Socketed discharge Level 3 1b Air discharge Level 3 Executive standard：IEC61000-4-2
Operating Environment	Operation Temperature	0~55℃
	Storage Temperature	—20~70℃
	Relative Humidity (non-condensing)	0~95%
Product	Dimension (L×W×H) Material Color Weight	156mm×79mm×17mm Aluminum alloy Black 205g
Reliability (MTBF)		>30000 hours

HDMI splitter function:





