

Model Number 52000C Multi-functions CCTV Tester TECHNOLOGY

Description:

The 7 inch IPS touch screen IP camera tester is designed for maintenance and installation of new 8K H.265 IP, analog, HD coaxial cameras as well as other security equipment, Support H.265/H.264 decoding camera, 8K video display via mainstream. The 1280x800 resolution enables it to display network HD cameras and analog cameras in high resolution. The unit supports many ONVIF PTZ and analog PTZ control. Additionally, it with other PoE power, UTP cable test and network tools etc. CCTV installers often need to carry a variety of testing tools to complete their work. If take the all in one camera tester, making working conditions safer and increasing productivity.



לצפייה באתר לחץ כאן

Features:

- 7 inch IPS touch screen, 1280*800 resolution
- 8K H.265 video display via mainstream
- 8MP TVI test, 3840 x 2160P 15 FPS, 4xzoom, video record & playback, coaxial PTZ control & call OSD menu
- 8MP AHD test, 3840 x 2160P 15 FPS, 4xzoom, video record & playback, coaxial PTZ & call OSD menu
- 8MP CVI test, 3840 x 2160P 12.5/15 FPS, 4xzoom, video record & playback, coaxial PTZ & call OSD menu
- Auto HD app, auto recognize HD coax camera type and resolution, support snapshot, video record & playback, coaxial PTZ & call OSD menu.
- HDMI Input, up to 4K 30FPS, and support snapshot, video record & playback
- Rapid ONVIF, Auto log in and display image, one-key create testing report, including camera IP address, resolution, encoding and other related information; support cross-network segment test; audio and video synchronization test; face recognition etc; NEW
- AXIS, Hikvision camera test, enter ONVIF app, input username and password to test
- IPC TEST (Non-ONVIF test), HIK test tool (Hikvision camera), DH test tool (Dahua camera)
- Video level meter, peak video signal level, SYNC signal level, Color bar chroma level measurement
- DC12V/3A power output, DC24V 2A power output
- DC5V 2A power output, can connect USB camera, USB and Mouse, as power bank
- 48V PoE power output power, max power 30W
- Rapid video, just by one key to detect all network cameras and auto display
- Built in Wi-Fi Analysis, support 2.4G/5G frequency band, can test Wi-Fi camera, create Wi-Fi hotspot

Cable test:

- Improvement cable tester, UTP cable, telephone cable etc order and connectivity test, can save testing report, if special number, need customized · and detect near-end, mid-end and far-end fault test of RJ45 cable plug
- RJ45 cable TDR test, test cable pair status, length, attenuation, reflectivity, impedance, skew etc.
- Digital Cable tracer, search BNC cable, network cable and telephone cable from the mess cables, more accurately

Specifications:

Item series		Multi-functions CCTV Tester TECHNOLOGY	
LCD	Display	New 7 inch IPS touch screen, 1280*800 resolution	
Video Mode	CVBS	IP Discovery/Quick ONVIF/IPC test /RTSP play /Client APK	
		Analog camera testing	
		PTZ control, RS485 control, Baud 600-115200bps, compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic etc	
	IP camera test 8K H.265/4K H.264	IP Discovery/Quick ONVIF/IPC test /RTSP play / Auto HD , automatically recognize type of HD input signal	
		Rapid Video	Auto view the video, create testing report
		Hik test tool	Support batch activate HIKVISION cameras and modify IP address, modify password etc. etc.
		Dahua test tool	Support batch activate DAHUA cameras and modify IP address, username and password. Self-defined modify channel name.
	Coaxial HD test	8MP TVI camera test,3840 x 2160P 15 FPS, UTC control & call OSD menu	
		8MP CVI camera test,3840 x 2160P 12.5/15 FPS, UTC control & call OSD menu	
		8MP AHD test, 3840 x 2160P 12.5/15 FPS, UTC control & call OSD menu	
	HDMI input and output	HDMI input support 4K 30FPS,HDMI output support 4K 60FPS	
	VGA input	Up to 1920*1200 60FPS	
	Zoom Image	4x zoom, enlarge image, Screen snapshot, record, save, view and record and play back	
Power output	PoE power output	48V PoE power output, max power 25.5W	
	DC24V/12V power	DC24V 2A, DC12V 3A power output	
	DC 5V power	DC5V 2A power output, can connect USB camera, USB and Mouse, as power bank	

Cable test	UTP cable test	Test UTP cable connection status and display on the screen. Read the number on the screen, and detect near-end, mid-end and far-end fault test of RJ45 cable plug
	Digital cable tracer	search BNC cable, network cable and telephone cable from the mess cables, more accurately
	RJ45 cable TDR test	Test cable pair status, length, attenuation, reflectivity, impedance, skew etc. measurement max range 180M
TesterPlay		Screen projection: Tester, mobile phone and PC display at the same time (For android version mobile phone)
Network test		Trace route, Link monitor, DHCP server, port flashing, Ping test
Wi-Fi		Built in WIFI, speeds 150M, display wireless camera image
Audio test		1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone
Data monitor		Captures and analyzes the command data from controlling device, also can send hexadecimal
PSE/PoE test		Measurement PoE switch or PSE power supply voltage and cable connection status
External power supply		DC 12V 2A
Battery		Built-in 7.6V 7800mAh, Lithium polymer battery, After fast charging 3.5 hours, normal working time 16 hours
Operation setting		OSD menu, select your desired language: English, Portuguese, Korean, Russian, Italian, French, Polish, Spanish, Japanese, Turkish, Deutsch, Serbain, Czech, Vietnamese etc
Auto off		5-30 (mins)
Working Temperature		-10°C---+50°C
Working Humidity		30%-90%
Dimension/Weight		276mm x 163mm x 44mm / 1.14KG

Packing kits:

			
Tester	Packing box	Tool bag	Lithium battery
			
Charger	Safety cord	Audio test cable	Power output cable
			
Rs485 Control cable	BNC cable	Cable tracer	

Wire:

