COMPANICS
Communication & Electronics LTD

כומפניקס תקשורת ואלקטרוניקה בע"מ
הבורסקאי 1 א.ת. סגולה, פ"ת | ספק מ. הביטחון: 83524121 | ח.פ: 512109968
03-9049004 טל' / | www.companics.co.il | sales@companics.co.il

Model Number 71000G
HDMI Matrix 2x2/2x4/4x2 (4K@60Hz)

Description:



The HDMI matrix 2x2/2x4/4x2 can connect 4 HD signal sources to 2 HD display terminals with optical fiber and stereo headphone output at the same time via HDMI out 1 port . The matrix allows four HDMI devices to be switched or split easily to two HDMI compatible monitors or projectors. Our devices offer solutions for noise, space and security concerns, data center control, information distribution, conference room presentation, school and corporate training environments.

לצפייה באתר לחץ כאן

Features:

- 5.4 inch IPS touch screen, 1920*1152 resolutions
- Support 3D video format
- Via HDMI out1, support 3.5mm earphone jack and optical output at same time
- 4 HDMI inputs switch and split to 2 HDMI displays;
- Support LPCM/Dolby/DTS 5.1 channel

Wire:



Specifications:

Item	HDMI Matrix 2x2/2x4/4x2 (4K@60Hz)		
Model	18351	18352	18353
Variation	2X2	2X4	4X2
HDMI resolution	3840*2160/60Hz		
Support video format	8/10/12 bit deep color		
Support audio format	LPCM/DTS/Dolby-AC3		
Max bandwidth	600MHz		
Max baud rate	3x6Gbps		
Input/ Output cable distance	4K/30Hz ≤15M AWG26 HDMI standard cable 4K/60Hz ≤5M HDMI 2.0 standard cable		
Max working current	900mA	750mA	900mA
Power adapter format	Input: AC (50HZ, 60HZ) 100V-240V; Output: DC5V/1.5A	Input: AC (50HZ, 60HZ) 100V-240V; Output: DC5V/1A	Input: AC (50HZ, 60HZ) 100V-240V; Output: DC5V/1.5A
Operating Temperature range	(-15 to +45℃)		
Operating Humidity range	5 to 90%RH (No Condensation)		
Dimension (L x W x H)	122x80x19 (mm)		
Weight	180g		