

Model Number 75500E SDI/HDMI video switcher for live streaming

Description:

SDI/HDMI video switcher for live streaming, 1 SDI input and 3 HDMI input support resolution 1080P@60Hz, and support HDCP1.4 standard, support HD embedded audio or external analog audio, after mixed processing, can be embedded in the output HD signal or output from the analog port. All resolution of the input signal is automatically adapted, the output resolution is 1920X1080@60Hz, To satisfy the requirements of Radio and television program production, live production of interviews and speeches, outdoor experience events, school courseware production and other video switching needs. It can be used in live streaming and various event venues.



לצפייה באתר לחץ כאן

Features:

- 1 SDI signal input supports a resolution of 1920*1080/60hz, and supports 100m lossless transmission;
- Easy convert broadcast-level SDI signal;
- 3 HDMI input; 2 HDMI output;
- One Type-C 3.0 capture port, supports video format YUY2;
- Support OSD display input channel signal, resolution information, volume information;
- Support MIC,LINE IN,HD mixing output (LINE OUT fixed mixing output);
- Support HD audio following (fixed following PGM);
- Support LINE OUT and HD audio output;
- Support power-off save settings;
- High quality keys, color backlight design.

Specifications:

Item	SDI/HDMI video switcher for live streaming	
Model	17758	17759
Variation	Exclude SDI	Include SDI
HDMI In	4 Inputs	3 Inputs
SDI input resolution	x	1080P@60Hz
SDI transmission rate	x	2.97Gbps
SDI input cable length	x	Max 100 meters, using RG6 75R HD digital video cable

Item	SDI/HDMI video switcher for live streaming	
Model	17758	17759
HDMI input resolution	1080P@60Hz	
HDMI output resolution	1080P@60Hz	
Type-C 3.0 capture and push network traffic video format	YUY2, MJPEG	
Supports audio format	PCM	
The maximum bandwidth transmission	148.5MHz	
Maximum transmission rate	1.65 x3Gbps	
The input cable length	1080P/60Hz≤1 5 m AWG26 HDMI standard cable	
The output cable length	1080P/60Hz≤15 m AWG26 HDMI standard cable	
Maximum working current	0.85 A	
Power adapter specifications	Input AC(50Hz,60Hz)100V-240V; Output: DC/12V 2A	
Working temperature range	(-15°C to +55°C)	
Size	180x130x52(mm)	
Weight	557g	

Wire:

